



**ROND** spiralé - lisse

∅(mm)	150	200	250	260*	300	320*	350	400
	450	500	550	600	650	700	800	1000

Au-delà de 6m de hauteur, fabrication étudiée (épaisseur renforcée)

\* disponible uniquement en spiralé

**CARRE** angles chanfreinés

∅ (mm)	260	300	320	400	450	500	600	650	800
l (cm)	20x20	22x22	25x25	30x30	35x35	40x40	45x45	50x50	60x60

**RECTANGLE** angles chanfreinés

∅ (mm)	300	320	350	400	400	450	450	500	500	550
lxL (cm)	20x25	20x30	25x30	24x35	30x35	25x40	30x40	30x45	35x40	35x45
∅ (mm)	550	550	550	600	600	650	650	700	700	
lxL (cm)	30x50	35x50	40x45	25x57	40x50	30x60	35x60	40x60	50x60	

**CARRE** angles vifs

∅ (mm)	350	450	500	700	1000
l (cm)	25x25	30x30	35x35	50x50	70x70

**RECTANGLE** angles vifs

∅ (mm)	250	450	500	550	550	550	650
lxL (cm)	15x20	20x40	20x45	20x50	25x49	30x45	25x60

**PROFIL HEXAGONAL**

∅ (mm)	200	300	400	500	600	700	800
c (mm)	100	150	200	250	300	350	400

**PROFIL OCTOGONAL**

∅ (mm)	250	300	350	400	500	600	700	800
c (mm)	96	115	134	153	191	230	267	306

**CANNELURE EXTERIEURE**

D (mm)	200	250	300	350	400	450	500	550
∅ (mm)	250	300	350	400	450	500	550	600
d (mm)	40	44	50	50	50	50	50	50

**CANNELURE INTERIEURE**

D (mm)	200	250	300	350	400	450	500	550
d1 (mm)	250	300	350	400	450	500	550	600
d (mm)	30	40	50	50	50	50	50	50
∅ (mm)	300	350	400	450	500	550	600	650

**DEMI COLONNE**

Cylindrique avec joint de dilatation intégré de 20 ou 40 mm d'épaisseur